



Micro Commercial Components

Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311

Phone: (818) 701-4933

Fax: (818) 701-4939

2N3906

## Features

- Through Hole Package
- Capable of 600mWatts of Power Dissipation
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Marking: Type number

## PNP General Purpose Amplifier

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARACTERISTICS				
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage* ( $I_C=1.0mA$ , $I_B=0$ )	40		Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ( $I_C=10\mu A$ , $I_E=0$ )	40		Vdc
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ( $I_E=10\mu A$ , $I_C=0$ )	5.0		Vdc
$I_{BL}$	Base Cutoff Current ( $V_{CE}=30V$ , $V_{BE}=3.0V$ )		50	nAdc
$I_{CEX}$	Collector Cutoff Current ( $V_{CE}=30V$ , $V_{BE}=3.0V$ )		50	nAdc

### ON CHARACTERISTICS

$h_{FE}$	DC Current Gain* ( $I_C=0.1mA$ , $V_{CE}=1.0V$ ) ( $I_C=1.0mA$ , $V_{CE}=1.0V$ ) ( $I_C=10mA$ , $V_{CE}=1.0V$ ) ( $I_C=50mA$ , $V_{CE}=1.0V$ ) ( $I_C=100mA$ , $V_{CE}=1.0V$ )	60 80 100 60 30	300	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ( $I_C=10mA$ , $I_B=1.0mA$ ) ( $I_C=50mA$ , $I_B=5.0mA$ )		0.25 0.4	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ( $I_C=10mA$ , $I_B=1.0mA$ ) ( $I_C=50mA$ , $I_B=5.0mA$ )	0.65	0.85 0.95	Vdc

### SMALL-SIGNAL CHARACTERISTICS


$f_T$	Current Gain-Bandwidth Product ( $I_C=10mA$ , $V_{CE}=20V$ , $f=100MHz$ )	250		MHz
$C_{obo}$	Output Capacitance ( $V_{CB}=5.0V$ , $I_E=0$ , $f=100MHz$ )		4.5	pF
$C_{ibo}$	Input Capacitance ( $V_{BE}=0.5V$ , $I_C=0$ , $f=100kHz$ )		10.0	pF
NF	Noise Figure ( $I_C=100\mu A$ , $V_{CE}=5.0V$ , $R_S=1.0k\Omega$ , $f=10Hz$ to $15.7kHz$ )		4.0	dB

### SWITCHING CHARACTERISTICS

$t_d$	Delay Time	$(V_{CC}=3.0V$ , $V_{BE}=0.5V$ , $I_C=10mA$ , $I_{B1}=1.0mA$ )	35	ns
$t_r$	Rise Time		35	ns
$t_s$	Storage Time	$(V_{CC}=3.0V$ , $I_C=10mA$ )	225	ns
$t_f$	Fall Time	$I_{B1}=I_{B2}=1.0mA$	75	ns







\*Pulse Width  $\leq 300\mu s$ , Duty Cycle  $\leq 2.0\%$

## TO-92



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.170	.190	4.33	4.83	
B	.170	.190	4.30	4.83	
C	.550	.590	13.97	14.97	
D	.010	.020	0.36	0.56	
E	.130	.160	3.30	3.96	
G	.010	.104	2.44	2.64	







[www.mccsemi.com](http://www.mccsemi.com)







# 2N3906



Micro Commercial Components



# 2N3906





Micro Commercial Components

**\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*APPLICATIONS DISCLAIMER\*\*\***

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.